Vanity basins - B6Q26BI


C€ EN 14688:2006

Cod. B6Q26BI


Basin 25x25 h12 cm. Sit-on installation. Fixing kit included. Weight 4,3 Kg.







	Wall mounted taps	Taps mounted on counter top
A:	130	105
B:	255	230
C:	380	355



* Per rubinetto su piano



BATAFORM®



CERASLIDE®

Cod. FI024BI

Valve drain with ceramic top for basins without overflow. Weight 0,5 Kg



Cod. FI024CR

Chromed valve drain for basins without overflow. Weight 0,5 Kg









Tips for proper cleaning Ceramic cleaning

We recommend the use of warm water in combination with non-abrasive cleaning products

Click to view or download



DOP N° L001-01



Is the result of years of research, on the glazes and the ceramic application, that ensures more protection, more resistance and ease of cleaning. The careful control of temperatures in the various cooking stages, in a cycle that can last up to 26 hours, ensures perfect homogeneity of the product during the sintering process, reducing porosity and guaranteeing greater resistance against stains, dirt and abrasions.



The antibacterial bataform treatment was developed to ensure deeper hygiene, basing its effectiveness on the reaction of silver ions, which inhibit the proliferation of bacteria. tests carried out by certified laboratories, according to the uni4543 standard, have confirmed a drastic decrease in the presence of bacteria, without however altering the glossy glaze. for cleaning operations, follow the recommendations given for the ceraslide glaze.